

Rec'd PCT/PTO 16 FEB 2005  
PCT/CA 03/01217

22 SEPTEMBER 2003 22.09.03  
X2

REC'D 10 OCT 2003

WIPO PCT

PA 1051298

# THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

August 12, 2003

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM  
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK  
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT  
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A  
FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/403,642

FILING DATE: August 16, 2002

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)



By Authority of the  
COMMISSIONER OF PATENTS AND TRADEMARKS

*T. Wallace*  
T. WALLACE  
Certifying Officer

Best Available Copy

**08/16/02**

Apple


PTO/SB/16 (10-01)

Patent and Trademark Office U.S. DEPARTMENT OF COMMERCE

# PROVISIONAL APPLICATION FOR PATENT COVER SHEET

**This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).**

Express Mail Label No.

INVENTOR(S)			
Given Name (first and middle (if any))	Family Name or Surname	Residence (City and either State or Foreign Country)	
Herbert André	JANSEN	Montréal, Québec, Canada	
<input type="checkbox"/> Additional Inventors are being named on the _____ separately numbered sheets attached hereto			
<b>TITLE OF THE INVENTION (500 characters max)</b>			
<b>INTERFACE APPARATUS FOR PASSIVE TRACKING SYSTEMS AND METHOD OF USE THEREOF</b>			
Direct all correspondence to:		<b>CORRESPONDENCE ADDRESS</b>	
<input checked="" type="checkbox"/> Customer Number	020988	 <b>020988</b> <small>PATENT AND TRADEMARK OFFICE</small>	
<input type="checkbox"/> Firm or Individual Name		Type Customer Number here	
Address			
Address			
City		State	
Country		Telephone	
		ZIP	
		Fax	
<b>ENCLOSED APPLICATION PARTS (check all that apply)</b>			
<input checked="" type="checkbox"/> Specification Number of Pages	10	<input type="checkbox"/> CD(s), Number	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets	2	<input type="checkbox"/> Other (specify)	
<input type="checkbox"/> Application Data Sheet, See 37 CFR 1.76			
<b>METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT</b>			
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27		FILING FEE AMOUNT (\$)	
<input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fee		Cheque No. 010693	
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing Fees or credit any overpayment to Deposit Account Number:		19-5113	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached		<b>\$160.00</b>	
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government			
<input checked="" type="checkbox"/> No.			
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____			

***Respectfully submitted,***

**SIGNATURE**

TYPED or PRINTED NAME

**Robert CARRIER**

TELEPHONE

**(514) 847-4252**

Date \_\_\_\_\_

**August 15, 2002**

**REGISTRATION NO.**  
*If appropriate)*

**30,726**

**Docket Number:**

15228-9uspr JA/PAN/df

**USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT**

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14.

[ISOR.PAT.FORM 110 – 10/2001]

**INTERFACE APPARATUS  
FOR PASSIVE TRACKING SYSTEMS  
AND METHOD OF USE THEREOF**

**FIELD OF THE INVENTION**

- [001] The present invention generally relates to optical tracking systems and, more particularly but not exclusively, to interaction between a tool operator and a tracking system.

**BACKGROUND OF THE INVENTION**

- [002] There are many advantages to being able to operate a computer-aided surgery (CAS) system in an operating room. For a system that allows real-time display of the relative positions of three-dimensional models of anatomical structures and of a surgical tool by tracking of the latter, this means being able to select a component or section of an image displayed on a monitor and perform operations on it such as zooming in and out, rotating it, etc. It also means enabling a surgeon to digitize points, whereby the latter may, for instance, define a profile of an operated bodily part.
- [003] The interaction between the surgeon and the CAS system presents some difficulties. For one thing, the surgeon operates in a sterile zone, whereas components of the CAS system are in a non-sterile zone. To perform some computer-related operations, such as controlling the monitor displays, the surgeon is required to interact with the CAS system. For instance, the act of selecting an object on a screen is typically done with a computer mouse, the mouse directing a visible cursor to the desired point on the image. However, due to the need for all objects in the sterile zone of the operating room to be sterile, a mouse cannot be used in the sterile zone to perform such actions.
- [004] In order to get around the fact that a mouse is not sterile, it is possible to have a person other than the surgeon interacting with the CAS system. In this case, the surgeon, or other person manipulating a surgical tool, needs to verbalize very

specific instructions to the person interacting with the CAS system in order to obtain the desired results. This technique is both tedious and inefficient.

- [005] Since the field of interactive CAS systems is relatively new, there is no prior art that covers the concept of providing an interface within the sterile zone by which the surgeon may interact with the CAS system by way of a tracking system.

#### **SUMMARY OF THE INVENTION**

- [006] It is an object of the present invention to provide a sterile interface for interaction with CAS systems.
- [007] It is another object of the present invention to provide an interface for interaction with a CAS system as a function of a tracking of a tool.
- [008] Therefore, in accordance with the present invention, there is provided an interactive tracking system for tracking a position and orientation of a tool and for interaction with an operator of the tool in computer-assisted surgery, the interactive tracking system comprising a detectable device trackable for position and orientation and adapted to be mounted to a tool; an interaction device adapted to be mounted to the tool and actuatable to send an interaction signal relating to a function of the tool; a tracking system for tracking the detectable device for position and orientation; and a computer-assisted surgery system connected to the tracking system for calculating a position and orientation of the tool as a function of the tracking of the detectable device and for initiating an interaction as a function of the position and orientation of the tool when receiving the interaction signal.
- [009] Further in accordance with the present invention, there is provided a passive optical interface apparatus for tracking by a tracking system of an object in space for position and orientation and for interacting with the tracking system, the passive optical interface apparatus comprising at least three passive detectable devices trackable for position by the tracking system; and a mounting device for receiving the three passive detectable devices in a known geometry and adapted for being secured to the object such that a position and orientation of the object is calculable by the tracking system as a function of a tracking of the known geometry of the

passive detectable devices, at least a first one of the passive detectable devices being displaceable with respect to the object, a displacement of said first one of the passive detectable devices with respect to the object being detectable to initiate an interaction with the tracking system while maintaining the tracking of the object.

- [010] Still further in accordance with the present invention, there is provided a method for interaction between a tracking system tracking a position and orientation of an object in space and a handler of the object, the object having at least one detectable device with at least two detectable configurations, comprising the steps of: i) tracking a position and orientation of the detectable device for calculating a position and orientation of the object as a function of the position and orientation of any one of the detectable configurations of the detectable device; ii) interpreting a change between the detectable configurations as an interaction signal from the handler; and iii) responding to the interaction signal by initiating an interaction response to the handler.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

- [011] These and other features, aspects and advantages of the present invention will become better understood with regard to the following description and accompanying drawings wherein:
- [012] FIG. 1 is a perspective view of a surgical instrument having a computer interface device in accordance with the present invention;
- [013] FIG. 2 is an enlarged fragmented side elevational view of the computer interface device;
- [014] FIG. 3 is a schematic representation of an interactive tracking system in accordance with the present invention; and
- [015] FIG. 4 is a block diagram illustrating a method for interaction between the interactive tracking system and a tool operator, in accordance with the present invention.

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

- [016] Referring now to Fig. 1, a tool is generally shown at S. It is pointed out that the tool S may take a plurality of forms. The tool S has a working tip T at an end of a working shaft W and a handle portion H. A blade 10 is secured to the tool S. More precisely, the blade 10 is positioned adjacent to the junction between the handle portion H and the working shaft W. The blade 10 comprises detectable spheres 12, 14 and 16. An interface apparatus is generally shown at 20 and is positioned at an end of the working shaft W adjacent to the handle portion H. It is pointed out that the interface apparatus 20 may be positioned elsewhere on the tool S, but is preferably within reach of the fingers of the surgeon. The interface apparatus 20 has a detectable sphere 22 which is mounted at an end of a lever 24. As shown in Figs. 1 and 2, the lever 24 may move between a first position, as shown by P1, and a second position, as shown by P2. The lever 24 may be biased such that the detectable sphere 22 remains, for instance, at position P1. Accordingly, when the lever 24 is moved to P2, the lever 24 returns automatically to position P1.
- [017] The detectable spheres 12, 14, 16 and 22 are each coated with a retro-reflective layer in order to be detected by, for instance, an infrared sensor using axial illumination. It is pointed out that other shapes could be used as alternative embodiments to retro-reflective spheres. As an example, straight cylinders, corner reflectors or the like having retro-reflective properties could also be used. It is preferred that the detectable devices be passive, such that they are wireless. In surgical applications, having wires connecting a CAS to a surgical tool could create sterility issues, as the wires require to extend out of the sterile zone. It is obviously possible to use active detectable devices, such as wireless magnetic sensors.
- [018] The detectable sphere 14 is shown removed from the blade 10. The detectable spheres 12, 16 and 22 may also be removed from the tool S, as each sphere is snap-fitted to an adaptor. One such adaptor is shown at 15 in Fig. 1. Therefore, single-use sterilized spheres may be used, or other spheres which may be sterilized with processes milder than autoclave sterilization (which is typically used for sterilizing surgical tools and instruments), whereby a retro-reflective coating does not need to be characterized by its capability to sustain high temperatures or pressures.

The tool S is preferably of materials adapted to be sterilized through an autoclave process.

[019] The detectable spheres 12, 14 and 16 represent a geometrical pattern used for the tracking of the surgical tool S and will be referred to hereinafter as geometrical pattern 12-14-16. The detectable spheres 12, 14 and 16 are tracked by optical sensors of an interactive tracking system 18, which recognizes the pattern 12-14-16 and knows the relation of the pattern 12-14-16 with respect to the tool S. Therefore, the position and orientation of the tool are calculable as a function of the tracking of the pattern 12-14-16. The detectable spheres 12, 14 and 16 thus allow for all six degrees of freedom of the surgical tool S to be known when the surgical tool S is displaced in the working range of the interactive tracking system 18.

[020] In a first embodiment of the present invention, the detectable sphere 22 is used with two of the three spheres on the blade 10 in order to make another optically detectable geometrical pattern. For instance, detectable spheres 12, 14 and 22 form a geometrical pattern (hereinafter referred to as pattern 12-14-P1) when the detectable sphere 22 is at position P1. The geometrical pattern 12-14-P1 is tracked for position and orientation simultaneously with the tracking of the geometrical pattern 12-14-16. As the tool S and all detectable spheres thereon are tracked for position and orientation, a move of the detectable sphere 22 from position P1 to position P2 will modify the optical pattern 12-14-P1, and this will be detected by the interactive tracking system 18. The modification detected by the interactive tracking system 18 will be interpreted as an interaction signal thereby. Accordingly, the tool operator is enabled to send a signal to the interactive tracking system 18 by flicking the lever 24 out of position P1, and this is equivalent to a "click" of a mouse button. It is also possible to use a third pattern, with the detectable sphere 22 held in position P2, and referred to as pattern 12-14-P2. The two patterns, 12-14-P1 and 12-14-P2, enable the operator to use a time dimension (as opposed to a click). For instance, pattern 12-14-P1 may represent an OFF position, while pattern 12-14-P2 represents an ON position. Therefore, this ON/OFF switching may be linked to various functions in the CAS system. It is pointed out that the optical patterns 12-14-16, 12-14-P1 and 12-14-P2 must each be different from one another. Furthermore, all patterns defined by the detectable sphere 22 moving from P1 to P2

must not be similar to the pattern 12-14-16, in order for the sensor not to confuse the patterns one for another.

[021] In a second embodiment of the present invention, a vector is defined between the detectable sphere 22 at one position and one of the detectable spheres 12, 14 and 16. For instance, having detectable sphere 12 as the reference point, a vector is defined between the detectable sphere 22 at position P1 and the detectable sphere 12, and is referred to as vector 12-P1. A modification of the vector 12-P1 by a displacement of the detectable sphere 22 is detected by the interactive tracking system 18 of the CAS system, which will then send a signal to the CAS system. It is pointed out that a vector 12-P2 (i.e., with the detectable sphere at position P2) may be used as a second position and orientation, similar to the ON/OFF switching described above.

[022] The interactive tracking system 18 is typically an optical tracking system capable of tracking the real-time position and orientation of at least three detectable devices in a working space. However, although the preferred embodiments of the present invention incorporate passive detectable devices (i.e., the detectable spheres 12, 14, 16 and 22), the tracking system 18 may be an active tracking system. Referring to Fig. 3, the various components of the interactive tracking system 18 are schematically shown. The interactive tracking system 18 is mainly composed of a tracking system 40 and a CAS system 48 in operative relation therewith, the CAS system 48 having an interaction signal interpreter. The tracking system 40 consists of a position calculator 42 connected to sensors 44 to track detectable devices on a tool or object for position and orientation. The position calculator 42 is typically connected to peripheral 46, such as a monitor, a keyboard and a mouse. The interaction signal interpreter of the CAS system 48 is programmed to detect the interaction signals, e.g., as set forth in the first and second embodiments of the present invention, such that the interactive tracking system 18 may initiate an interaction with the tool operator, or object handler. The interaction between the interactive tracking system 18 and the tool operator can be a function of the position and orientation of the tool being tracked. For instance, zooming actions may take place on the monitor of the peripherals 46. The tool can be a pointer, whereby points in space may be digitized using the interaction signals to indicate points (e.g.,



registration of a bone by a pointer in CAS). A menu may be presented to a tool operator on a monitor of the peripherals 46.

[023] As mentioned previously, it is preferred that the tracking system 40 be an optical tracking system, to operate the interactive tracking system 18 with the interface apparatus 20 described above. However, the correlation between the tracking of an object for position and orientation, and the interaction between the interactive tracking system 18 and the object handler/tool operator is a feature of the present invention that is not to be limited to the use of passive tracking. When an optical tracking system 40 is used, the Polaris® Optical Tracking System by Northern Digital Inc. is suitable for such purposes. It is pointed out that the detectable spheres 12, 14, 16 and 22 must be positioned on the tool S in compliance with the requirements of the interactive tracking system 18. For example, the Polaris® Optical Tracking System requires that the detectable spheres are separated from one another by at least 5 cm. It is also a requirement for this tracking system that each segment between detectable spheres must differ from the other segments by at least 5 mm.

[024] Referring to Fig. 4, the actions on the interactive tracking system 18 and the interface apparatus 20 are illustrated at 50. According to step 52, a detectable device secured to an object in a detectable configuration is tracked for position and orientation. According to step 53, a position and orientation of the object is be calculated as a function of the tracking of the detectable device. According to step 54, a change in detectable configuration is interpreted as an interaction signal. Step 52 is independent from step 54 and is continuous, whereby the detectable device is tracked for position and orientation for any detectable configuration thereof and is not interrupted by step 54. According to step 56, an interaction response is initiated to respond to the interaction signal of step 54. The interaction response may be a function of the position and orientation of the object.

[025] The above-described interface apparatus 20 may be used with other typical elements of the CAS system, such as, for instance, a calibration base having detectable spheres configured similarly to the above-described embodiments. The signal of a movable sphere detected by the sensor 18 may be used for the CAS system to take a calibration reading.

- [026] Having the interface apparatus 20 on the surgical tool S is advantageous, as the surgeon is no longer required to move out of his sterilized zone in order to interact with the CAS system. It is pointed out that the detectable sphere 22 is not restricted to two positions and, therefore, a plurality of various positions may allow the tool operator to interface with the computer in many various ways.
- [027] Also, the present invention is not restricted to using lever 24 as the interface device 22. A switch sliding between positions, an indexed disk, a push button or the like may be used as long as a detectable element is displaceable on the surgical tool S between at least first and second positions and orientations. Although the use of four detectable spheres, one of which is moveable, is preferred, other ways of providing a signal detectable by the interaction signal interpreter 48 are considered. For instance, a mechanism can be provided that would enable a precise and detectable motion of a pattern of the detectable spheres with respect to the tool, such as a quick tilt. There is however a risk that the given motion be inadvertently executed by an operator. Also, two active sensors can be provided onto the tool, with one of the sensors being displaceable with respect to the tool while the other one is immovable with respect to the tool. A relative displacement between the active sensors can thereafter be used to initiate an interaction signal between a CAS system and a surgeon, with the immovable active sensor being continuously tracked for position and orientation so as to have a continuous tracking of the tool.

**WHAT IS CLAIMED IS:**

1. An interactive tracking system for tracking a position and orientation of a tool and for interaction with an operator of the tool in computer-assisted surgery, the interactive tracking system comprising:

a detectable device trackable for position and orientation and adapted to be mounted to a tool;

an interaction device adapted to be mounted to the tool and actuatable to send an interaction signal relating to a function of the tool;

a tracking system for tracking the detectable device for position and orientation; and

a computer-assisted surgery system connected to the tracking system for calculating a position and orientation of the tool as a function of the tracking of the detectable device and for initiating an interaction as a function of the position and orientation of the tool when receiving the interaction signal.

2. A passive optical interface apparatus for tracking by a tracking system of an object in space for position and orientation and for interacting with the tracking system, the passive optical interface apparatus comprising:

at least three passive detectable devices trackable for position by the tracking system; and

a mounting device for receiving the three passive detectable devices in a known geometry and adapted for being secured to the object such that a position and orientation of the object is calculable by the tracking system as a function of a tracking of the known geometry of the passive detectable devices, at least a first one of the passive detectable devices being displaceable with respect to the object, a displacement of said first one of the passive detectable devices with respect to the object being detectable to initiate an interaction with the tracking system while maintaining the tracking of the object.

3. A tracking system for tracking a position and orientation of an object having a passive optical interface apparatus according to claim 2 secured thereto and for interaction with a handler of the object, the tracking system comprising:

a passive optical tracking system for tracking a position and orientation of the known geometry of the passive detectable devices and for calculating a position and orientation of the object as a function of the known geometry; and

an interaction signal interpreter connected to the passive optical tracking system for detecting a displacement of said first one of the passive detectable devices with respect to the object to initiate an interaction signal of the tracking system with the handler.

4. A method for interaction between a tracking system tracking a position and orientation of an object in space and a handler of the object, the object having at least one detectable device with at least two detectable configurations, comprising the steps of:

i) tracking a position and orientation of the detectable device for calculating a position and orientation of the object as a function of the position and orientation of any one of the detectable configurations of the detectable device;

ii) interpreting a change between the detectable configurations as an interaction signal from the handler; and

iii) responding to the interaction signal by initiating an interaction response to the handler.

5. The method according to claim 4, wherein the interaction response is a function of the position and orientation of the object.




FIG. 1

FIG. 2




FIG. 3.




FIG. 1

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**